


LAB EQUIPMENT **CATALOGUE**









VITIS & WINEMAKERS

NZ Office & Shop: 24-26 Herbert St, Mayfield, Blenheim. New Zealand Phone: +64 3 577-8778

Head Office:

96 Chifley Drive, Preston. VIC. Australia Phone: +61 (03) 9487-1160

info@vitiswinemakers.com www.vitiswinemakers.com

| Product | Page |
|---|------|
| Adaptors and Joints | 3 |
| Auto Pipettes | 7 |
| Auto Pipette Tips | 7 |
| Beakers | 8 |
| Bottle-Dropping | 10 |
| Bottle-Drying Tower | 11 |
| Bottle-Gas Washing | 12 |
| Bottle-Reagent | |
| Bottle-Screw Cap | |
| Bottle-Weighing | 16 |
| Burettes | 17 |
| Condensers | |
| Crucible | 20 |
| Desiccators | |
| Dishes - Crystallising etc | |
| Distillation | |
| Emission Testing | |
| Evaporating Dishes | |
| Environmental chambers, ovens, water baths and incubators | |
| Flasks Boiling | |
| Flasks Conical | |
| Flasks Filtering | |
| Flasks Volume | |
| Funnels | |
| Hydrometers | |
| Jacket Tubes | |
| Magnetic Stir Bars | |
| Measuring Cylinders | |
| Miscellaneous | |
| Mortar | |
| Panel Testing | |
| Petri Dish | |
| Pipettes | |
| Seperating Funnel | |
| Slides | |
| Stands and Accessories | |
| Stands and Accessories | |
| Stirrers | |
| Stoppers | |
| Test tubes | |
| Thermometers | |
| Watchglasses | 48 |

Adaptors and Joints

| Code | Description |
|---------|---|
| 5077-01 | Adaptor - Expansion - big socket - small cone - 14/23, 10/19 |
| 5077-02 | Adaptor - Expansion - big socket - small cone - 19/26, 10/19 |
| 5077-03 | Adaptor - Expansion - big socket - small cone - 19/26, 14/23 |
| 5077-04 | Adaptor - Expansion - big socket - small cone - 24/29, 10/19 |
| 5077-05 | Adaptor - Expansion - big socket - small cone - 24/29, 14/23 |
| 5077-06 | Adaptor - Expansion - big socket - small cone - 24/29, 19/26 |
| 5077-07 | Adaptor - Expansion - big socket - small cone - 29/32, 19/26 |
| 5077-08 | Adaptor - Expansion - big socket - small cone - 29/32, 24/29 |
| 5073-01 | Adaptor - one cone - one straight - 10/19 Adaptor - one cone - one straight - 10/19, length of upper tube 40mm |
| 5073-02 | Adaptor - one cone - one straight - 14/23 length of upper tube 40mm |
| 5073-03 | Adaptor - one cone - one straight - 19/26 length of upper tube 45mm |
| 5073-04 | Adaptor - one cone - one straight - 24/29 length of upper tube 55mm |
| 5073-05 | Adaptor - one cone - one straight - 29/32 length of upper tube 60mm |
| 5073-06 | Adaptor - one cone - one straight - 34/35 length of upper tube 60mm |
| 5073-07 | Adaptor - one cone - one straight - 40/38 length of upper tube 60mm |

| Code | Description |
|----------------|--|
| 5076-01 Broat | Adaptor - Reduction - small socket - big cone - 10/19, 14/23 |
| 5076-02 | Adaptor - Reduction - small socket - big cone - 10/19, 19/26 |
| 5076-03 | Adaptor - Reduction - small socket - big cone - 10/19, 24/29 |
| 5076-05 | Adaptor - Reduction - small socket - big cone - 14/23, 24/29 |
| 5076-06 | Adaptor - Reduction - small socket - big cone - 14/23, 29/32 |
| 5076-08 | Adaptor - Reduction - small socket - big cone - 19/26, 29/32 |
| 5076-09 | Adaptor - Reduction - small socket - big cone - 19/26, 34/35 |
| 5076-10 | Adaptor - Reduction - small socket - big cone - 24/29, 29/32 |
| 5076-11 | Adaptor - Reduction - small socket - big cone - 24/29, 34/35 |
| 5076-12 | Adaptor - Reduction - small socket - big cone - 24/29, 40/38 |
| 5076-13 | Adaptor - Reduction - small socket - big cone - 24/29, 50/42 |
| 5076-14 | Adaptor - Reduction - small socket - big cone - 29/32, 34/35 |
| 5076-15 | Adaptor - Reduction - small socket - big cone - 29/32, 40/38 |
| 5055-02 | Adaptor 105 bent - 14/23 |
| 5055-02 | Adaptor 105 bent - Long - 14/23 Length 190mm |
| 5067-1 | Adaptor stopper - bent - standard ground mouth 10/19 with 6mm OD upper tube. |

| Code | Description |
|---------|---|
| 1224-7A | Connection tube - T shape - 8 mm external, T joiner |
| 1224-7C | Connection tube - Y shape - rounded top - 8 mm |
| 1224-7B | Connection tube - Y shape - 8 mm external |
| 5071-01 | Joiner - dual cone - 10/19,10/19 |
| 5071-02 | Joiner - dual cone - 14/23,14/23 |
| 5071-03 | Joiner - dual cone - 19/26,19/26 |
| 5071-04 | Joiner - dual cone - 24/29,24/29 |
| 5071-05 | Joiner - dual cone - 29/32,29/32 |
| 5071-06 | Joiner - dual cone - 34/35,34/35 |
| 5071-07 | Joiner - dual cone - 40/38,40/38 |

| Code | Description |
|---|---|
| 5072-01 Book Barrier | Joiner - dual socket - 10/19,10/19 |
| 5072-02 | Joiner - dual socket - 14/23,14/23 |
| 5072-03 | Joiner - dual socket - 19/26,19/26 |
| 5072-04 | Joiner - dual socket - 24/29,24/29 |
| 5072-05 | Joiner - dual socket - 29/32,29/32 |
| 5072-06 | Joiner - dual socket - 34/35,34/35 |
| 5072-07 | Joiner - dual socket - 40/38,40/38 |
| 5052-02 | Receiving tube 105 - 14/23, 14/23 |
| 5033-03 | Two mouth Connection tube |
| 3033-03 | Two mouth Connection tube - standard ground mouth. Middle ground mouth - 19/26 Side ground mouth - 19/26 Bottom ground stopper - 19/26 |
| 5053-02 | Vacuum receiving tube 105 - 14/23, 14/23 |

Auto Pipettes

| Code | Description |
|--------|---|
| H10 | Auto Pipette - 1 - 10µl |
| | 1 - 10µl capacity. Package contains 14 disposable tips. |
| | This pipette uses the principles of suction and drainage, with the amount of travel of the moving piston - and thereby the quantity of liquid withdrawn - controlled by an adjustable wheel built into the pipette. |
| H100 | Auto Pipette - 10 - 100μl |
| 11100 | 10 - 100μl capacity. Package contains 14 disposable tips. |
| | |
| H1000 | Auto Pipette - 100 - 1000µl |
| 111000 | 100 - 1000µl capacity. Package includes 9 disposable tips. |
| H5000 | Auto Pipette - 1000 - 5000µl |
| 113000 | 1000 - 5000µl capacity. Package includes 2 disposable tips. |
| H10ml | Auto Pipette - 10ml |
| H20 | Auto Pipette - 2 - 20µl |
| | 2 - 20µl capacity. Package contains 14 disposable tips. |
| H200 | Auto Pipette - 20 - 200μl |
| | 20 - 200µl capacity. Package contains 14 disposable tips. |

Auto Pipette Tips

| Code | Description |
|------------|--|
| P10 Tips | Pipette Tips 0.1 - 10μl - Pack of 1000 |
| P10ml Tips | Pipette Tips 1-10ml - Pack of 100 |
| P1000 Tips | Pipette Tips 100 - 1000μl - Pack of 500 |
| P5000 Tips | Pipette Tips 1000 - 5000μl - Pack of 100 |
| P200 Tips | Pipette Tips 2 - 200μl - Pack of 1000 |

Beakers

| Code | Description |
|--|--|
| 3101-0025 | Beaker - micro - 0025 ml |
| | With spout and graduations. |
| | Made from high quality borosilicate glass with a silica content of 80%, this glassware possesses marked mechanical strength and very high resistance against chemical attacks. Furthermore, its low linear coefficient of thermal expansion makes it capable of withstanding high levels of thermal shock. |
| | Image is example only |
| 1101-0050 | Beaker - short - 0050 ml |
| 1101 0050 | With spout and graduations. |
| 200 mm mod mod mod mod mod mod mod mod mod | Made from high quality borosilicate glass with a silica content of 80%, this glassware possesses marked mechanical strength and very high resistance against chemical attacks. Furthermore, its low linear coefficient of thermal expansion makes it capable of withstanding high levels of thermal shock. |
| | Image is example only |
| 1101-0100 | Beaker - short - 100 ml |
| 1101-0150 | Beaker - short - 150 ml |
| 1101-0150-10 | Beaker - short - 0150 ml x 10 |
| | pack of 10 units |
| 1101-0200 | Beaker - short - 0200 ml |
| 1101-0250 | Beaker - short - 0250 ml |
| 1101-0250 | Beaker - short - 0250 ml - x 8 |
| 1101 0250 | Box of 8 |
| 1101-0300 | Beaker - short - 0300 ml |
| 1101-0400 | Beaker - short - 0400 ml |
| 1101-0400 | Beaker - short - 0400 ml x 10 Box of 10 |
| 1101-0800 | Beaker - short - 0800 ml |
| 1101-1000 | Beaker - short - 1000 ml |
| 1101-2000 | Beaker - short - 2000 ml |

| Code | Description |
|-----------|---|
| 1102-0100 | Beaker - tall - 0100ml |
| | With spout and graduations. |
| FRY Do 33 | Made from high quality borosilicate glass with a silica content of 80%, this glassware possesses marked mechanical strength and very high resistance against chemical attacks. Furthermore, its low linear coefficient of thermal expansion makes it capable of withstanding high levels of thermal shock. Image is example only |
| | image is example only |
| 1102-0150 | Beaker - tall - 0150 ml |
| 1102-0250 | Beaker - tall - 0250 ml |
| 1102-0400 | Beaker - tall - 0400 ml |
| 1102-0600 | Beaker - tall - 0600 ml |
| 1102-1000 | Beaker - tall - 1000 ml |

Bottle-Dropping

| Code | Description |
|----------|--|
| 1452-125 | Bottle - dropping - amber - ground in pipette - 125 ml |
| | |
| | |

Bottle-Drying Tower

| Code | Description |
|------|-------------------------------|
| | Bottle - Drying Tower - 500ml |
| | |

Bottle-Gas Washing

| Code | Description |
|----------|--|
| 1313-500 | Bottle - gas washing - Muenks - 500 ml |
| | |

Bottle-Reagent

| Code | Description |
|-----------|--|
| 1402-0125 | Bottle - reagent - amber - narrow mouth - with stopper - 0125 ml Image is example only |
| 1402-0250 | Bottle - reagent - amber - narrow mouth - with stopper - 0250 ml |
| 1402-0500 | Bottle - reagent - amber - narrow mouth - with stopper - 0500 ml |
| 1402-1000 | Bottle - reagent - amber - narrow mouth - with stopper - 1000 ml |
| 1404-0125 | Bottle - reagent - amber - wide mouth - with stopper - 0125 ml Image is example only |
| 1404-0250 | Bottle - reagent - amber - wide mouth - with stopper - 0250 ml |
| 1404-0500 | Bottle - reagent - amber - wide mouth - with stopper - 0500 ml |
| 1404-1000 | Bottle - reagent - amber - wide mouth - with stopper - 1000 ml |
| 1401-0125 | Bottle - reagent - clear - narrow mouth - with stopper - 0125 ml Image is example only |
| 1401-0250 | Bottle - reagent - clear - narrow mouth - with stopper - 0250 ml |
| 1401-0500 | Bottle - reagent - clear - narrow mouth - with stopper - 0500 ml |
| 1401-1000 | Bottle - reagent - clear - narrow mouth - with stopper - 1000 ml |

| Code | Description |
|-----------|---|
| 1403-0125 | Bottle - reagent - clear - wide mouth - with stopper - 0125 ml Image is example only |
| 1403-0250 | Bottle - reagent - clear - wide mouth - with stopper - 0250 ml |
| 1403-0500 | Bottle - reagent - clear - wide mouth - with stopper - 0500 ml |
| 1403-1000 | Bottle - reagent - clear - wide mouth - with stopper - 1000 ml |
| 1403-5000 | Bottle - reagent - clear - wide mouth - with stopper - 5000 ml |

Bottle-Screw Cap

| Code | Description |
|-------------|--|
| BOT-SCW-500 | Bottle-Screw Cap-500ml Bottle-Screw Cap- 500ml Borosilicate Glass 3.3 |

Bottle-Weighing

| Code | Description |
|-----------|---|
| 1302-2525 | Bottle - weighing - short - 25 X 25 mm Image is example only |
| 1302-5030 | Bottle - weighing - short - 50 X 30 mm |
| 1302-6030 | Bottle - weighing - short - 60 X 30 mm |
| 1302-7035 | Bottle - weighing - short - 70 X 35 mm |
| 1301-3030 | Bottle - weighing - tall - 30 X 30 mm |
| 1301-3050 | Bottle - weighing - tall - 30 X 50 mm |
| 1301-3070 | Bottle - weighing - tall - 30 X 70 mm |
| 1301-4570 | Bottle - weighing - tall - 45 X 70 mm |

Burettes

| Code | Description | n | | | | |
|-----------|-------------|-----------------------|-----------------------|-------------------|----------------|--------------------------------|
| 1644A-010 | Burette - b | lue line on mi | lk white back | - rubber tub | ing connection | n - 10 ml |
| | Capacity | Graduated Interval | Capacity tolerance | Flow rate | Waiting Time | Width of graduation line |
| | 10 ml | 0.05 ml | ±0.025 ml | 30-45 seconds | 30 seconds | ≤ 0.3 mm |
| 1644A-025 | Burette - b | lue line on mi | lk white back | - rubber tub | ing connection | n - 25 ml |
| | Capacity | Graduated Interval | Capacity tolerance | Flow rate | Waiting Time | Width of graduation line |
| | 25 ml | 0.1 ml | ±0.04 ml | 45-70 seconds | 30 seconds | ≤ 0.3 mm |
| 1644A-050 | Burette - b | lue line on mi | lk white back | - rubber tub | ing connection | - 50 ml |
| | Capacity | Graduated Interval | Capacity tolerance | Flow rate | Waiting Time | Width of graduation line |
| | 50 ml | 0.1 ml | ±0.05 ml | 45-70 seconds | 30 seconds | ≤ 0.3 mm |
| 1644A-100 | Burette - b | lue line on mi | lk white back | - rubber tub | ing connection | n - 100 ml |
| | Capacity | Graduated Interval | Capacity tolerance | Flow rate | Waiting Time | Width of graduation line |
| | 100 ml | 0.2 ml | ±0.1 ml | 70-100 seconds | 30 seconds | ≤ 0.3 mm |

| Code | Description | | | | | |
|-----------|-------------|-----------------------|-----------------------|------------------|----------------|--------------------------------|
| 1645A-050 | Burette - b | lue line on mi | lk white back | ground - stra | night stopcock | - 10 ml |
| | Capacity | Graduated Interval | Capacity tolerance | Flow rate | Waiting Time | Width of graduation line |
| 10 | 50 ml | 0.05 ml | ±0.05 ml | 60-90 seconds | 30 seconds | ≤ 0.3 mm |
| 1645A-025 | Burette - b | lue line on mi | lk white back | ground - stra | night stopcock | - 025ml |
| | Capacity | Graduated Interval | Capacity tolerance | Flow rate | Waiting Time | Width of graduation line |
| | 25 ml | 0.1 ml | ±0.1 ml | 60-90 seconds | 30 seconds | ≤ 0.3 mm |
| 1645A-050 | Burette - b | lue line on mi | lk white back | ground - stra | night stopcock | - 50 ml |
| | Capacity | Graduated Interval | Capacity tolerance | Flow rate | Waiting Time | Width of graduation line |
| | 50 ml | 0.1 ml | ±0.1 ml | 60-90 seconds | 30 seconds | ≤ 0.3 mm |
| 1645A-100 | Burette - b | lue line on mi | lk white back | ground - stra | ight stopcock | - 100 ml |
| | Capacity | Graduated Interval | Capacity tolerance | Flow rate | Waiting Time | Width of graduation line |
| | 100 ml | 0.2 ml | ±0.2 ml | 60-90 seconds | 30 seconds | ≤ 0.3 mm |
| 1642A-010 | Burette - s | traight stopco | ck - 010 ml | | | |
| | Capacity | Graduated Interval | Capacity tolerance | Flow rate | Waiting Time | Width of graduation line |
| | 10 ml | 0.05 ml | ±0.025 ml | 30-45 seconds | 30 seconds | ≤ 0.3 mm |

Condensers

| Code | Description |
|--|---|
| 1215-0300 | Condenser - Graham - coiled inner tube - 300 mm |
| | Condenser - Graham - coiled inner tube - 300 mm long Jacket, 20mm OD upper tube, 3.3dm2 cooling area, 480mm overall length. Ends not ground joints. |
| | Note: This is a restricted item. To ensure that purchases are for legal uses only, we ask that you contact us first for clearance. |
| 1215-0400 | Condenser - Graham - coiled inner tube - 400mm |
| 1215 0 100 | Condenser - Graham - coiled inner tube - 400 mm long Jacket, 22mm OD upper tube, 4.7dm2 cooling area, 590mm overall length. |
| 5021-200-2 | Condenser - Leibig - 200 mm - 19/26,19/26 |
| e e | Condenser straight shape, ground mouth, 1.0 dm2 cooling area, 200mm long jacket, 332mm total length, 19/26,19/26 |
| | |
| 1216-0400 | Condenser - Reflux - Dimroth - coiled inner tube - 400 mm long jacket |
| The state of the s | Upper tube 22mmOD, 7.3dm2 cooling area, 590mm overall length. Ends not ground |
| | Note: This is a restricted item. To ensure that purchases are for legal uses only, we ask that you contact us first for clearance. |
| 5024-0300-3 | Condenser - reflux with coiled inner tube - 300mm - 29/32, 29/32, ground ends |
| 5023-0300-6 | Condenser - with coiled inner tube - 300mm - 24/29, 24/29, ground ends |

Crucible

| Code | Description |
|---------|--|
| Cru-050 | Crucible - 050ml Crucible - 050ml- Porcelain |

Desiccators

| Code | Description |
|----------|--|
| 1351-210 | Desiccator - 210 mm |
| 1351-240 | Desiccator - 240 mm |
| 1354-240 | Desiccator - vaccuum - ground-in stopcock - 240 mm |

Dishes - Crystallising etc

| Code | Description |
|--------------|--|
| 1173-0125 | Crystallizing dish - with spout - 125 mm |
| JISA1460-DIS | JISA1460 Dish 115mm inside diameter 60mm height 115mm inside diameter |

Distillation

| Code | Description |
|-----------|---|
| 5035-09 | Distillation Head - all 19/26 |
| 5038-02 | Distilling Head 75° bent - 19/26 |
| | Distilling Head 75° bent - Straight ground stopper 19/26, oblique ground stopper 19/26 |
| 5038-03 | Distilling Head 75° bent - 24/29 |
| 3050 05 | Distilling Head 75° bent - Straight ground stopper 24/29, oblique ground stopper 24/29 |
| 1201-1506 | Distilling tube – plain |
| | Distilling tube - plain OD of main tube 15mm, OD of side tube 6mm, 200mm overall length. |

Emission Testing

| Code | Description |
|--------------|-------------------------------------|
| JISA1460-DIS | JISA1460 Dish 115mm inside diameter |
| | 60mm height 115mm inside diameter |

Evaporating Dishes

| Code | Description |
|----------|--|
| 1171-090 | Evaporating dish - flat bottom - 090 mm Image is example only |
| 1171-120 | Evaporating dish - flat bottom - 120 mm |
| 1171-150 | Evaporating dish - flat bottom - 150 mm |
| 1172-120 | Evaporating dish - round bottom - 120 mm |

Environmental chambers, ovens, water baths and incubators

| Code | Description | Price |
|------|--|-------|
| | Please phone us on 03 578 778 for details. | |

Flasks Boiling

| Code | Description |
|---------------------------|---|
| 5001-0010 | Flask-boil-1 neck-round bottom-0010ml-14/23 |
| 5001-0050 | Flask-boil-1 neck-round bottom-0050ml-24/29 |
| 5001-0100 | Flask-boil-1 neck-round bottom-0100ml-24/29 |
| 5001-0250 | Flask-boil-1 neck-round bottom-0250ml-24/29 |
| 5001-1000 | Flask-boil-1 neck-round bottom-1000ml-34/35 |
| 5001-2000 | Flask-boil-1 neck-round bottom-2000ml-34/35 |
| 5004-0500-4 | Flask-boil-3 neck-round bottom-0500mL-19/26,19/26,19/26 |
| 2004 0300 4 LET 1000mi | Note: This is a restricted item. To ensure that purchases are for legal uses only, we ask that you contact us first for clearance. |
| 5004-1000-4 | Flask-boil-3 neck-round bottom-1000mL-19/26, 24/29, 19/26 |
| 5005-0500-4 | Flask-boil-3 neck-round bottom-straight-0500ml-19/26, 24/29,19/26 |
| IN SOOM! | |
| 5005-3000-1 | Flask-boil-3 neck-round bottom-straight-3000ml-24/29,29/32,24/29 |
| LE 3000 | |
| 5006-1000-2 | Flask-boil-4 neck-round bottom-1000 ml 24/29, 3@19/26 |
| 12700 | |

Flasks Conical

| Code | Description |
|-----------------------|--|
| 1121-0100 | Flask - conical - Erlenmeyer - 100 ml With graduations. |
| | Made from high quality borosilicate glass with a silica content of 80%, this glassware possesses marked mechanical strength and very high resistance against chemical attacks. Furthermore, its low linear coefficient of thermal expansion makes it capable of withstanding high levels of thermal shock. |
| | Image is example only |
| 1121-0150 | Flask - conical - Erlenmeyer - 150 ml With graduations. |
| 1121-0200 | Flask - conical - Erlenmeyer - 200 ml With graduations. |
| 1121-0300 | Flask - conical - Erlenmeyer - 300 ml With graduations. |
| 1121-0500 | Flask - conical - Erlenmeyer - 500 ml With graduations. |
| 1121-1000 | Flask - conical - Erlenmeyer - 1000 ml With graduations. |
| 5009-0250-2 | Flask - conical - ground mouth - 0150 ml 24/29 |
| (LAT — 25.0 that | Quick fit conical flask - 150 ml |
| 5009-0250-2 | Flask - conical - ground mouth - 0250 ml 24/29 |
| | Quick fit conical flask - 250 ml |
| 1122-0050 | Flask - conical - ground mouth - with stopper - 0050 ml |
| | Made from high quality borosilicate glass with a silica content of 80%, this glassware possesses marked mechanical strength and very high resistance against chemical attacks. Furthermore, its low linear coefficient of thermal expansion makes it capable of withstanding high levels of thermal shock. |
| | Image is example only |
| 1122-0100 | Flask - conical - ground mouth - with stopper - 0100 ml |
| 1122-0250 | Flask - conical - ground mouth - with stopper - 0250 ml |
| 1122-0500 | Flask - conical - ground mouth - with stopper - 0500 ml |

| Code | Description |
|------------|---|
| 1121-0100 | Flask - conical - Erlenmeyer - Micro - 25 ml With graduations. |
| | Made from high quality borosilicate glass with a silica content of 80%, this glassware possesses marked mechanical strength and very high resistance against chemical attacks. Furthermore, its low linear coefficient of thermal expansion makes it capable of withstanding high levels of thermal shock. Image is example only |
| 1121-2000B | Flask - conical - Wide neck - 2000 ml With graduations. |
| | Made from high quality borosilicate glass with a silica content of 80%, this glassware possesses marked mechanical strength and very high resistance against chemical attacks. Furthermore, its low linear coefficient of thermal expansion makes it capable of withstanding high levels of thermal shock. Image is example only |

Flasks Filtering

| Code | Description |
|-----------|--|
| 1432-0250 | Flask - filtering - side tubulature - 0250 ml Image is example only |
| 1432-0500 | Flask - filtering - side tubulature - 0500 ml |
| 1432-1000 | Flask - filtering - side tubulature - 1000 ml |

Flasks Volume

| Code | Description |
|-------------|---|
| 1622A-0100 | Flask - volumetric - amber - with stopper - 0100 ml |
| | Capacity tolerance: ± 0.1 ml |
| | Width of graduation line: ≤ 0.4 mm |
| 1622A-0200 | Flask - volumetric - amber - with stopper - 0200 ml |
| 1022/(0200 | Capacity tolerance: ± 0.15 ml |
| | Width of graduation line: ≤ 0.4 mm |
| 1622A-0500 | Flask - volumetric - amber - with stopper - 0500 ml |
| | Capacity tolerance: ± 0.25 ml |
| | Width of graduation line: ≤ 0.4 mm |
| 1622A-1000 | Flask - volumetric - amber - with stopper - 1000 ml |
| | Capacity tolerance: ± 0.4 ml |
| | Width of graduation line: ≤ 0.4 mm |
| 1621A-0100 | Flask - volumetric - with stopper - 0100 ml |
| | Capacity tolerance: ± 0.10 ml |
| A STATE OF | Width of graduation line: ≤ 0.4 mm |
| | Image is example only |
| 1621A-0200 | Flask - volumetric - with stopper - 0200 ml |
| 1011/1 0100 | Capacity tolerance: ± 0.15 ml |
| | Width of graduation line: ≤ 0.4 mm |
| 1621A-0250 | Flask - volumetric - with stopper - 0250 ml |
| | Capacity tolerance: ± 0.15 ml |
| | Width of graduation line: ≤ 0.4 mm |
| 1621A-1000 | Flask - volumetric - with stopper - 1000 ml |
| | Capacity tolerance: ± 0.4 ml |
| | Width of graduation line: ≤ 0.4 mm |
| 1621A-2000 | Flask - volumetric - with stopper - 2000 ml |
| | Capacity tolerance: ± 0.6 ml |
| | Width of graduation line: ≤ 0.4 mm |

Funnels

| Code | Description |
|---------|---|
| Fun-100 | Buchner - Funnel - Porcelain - 100mm Buchner - Funnel - Porcelain - 100mm Perforated Filter Disc, Glazed |
| 1503-50 | Funnel - 60° approx - long stem - 50 mm diameter Image is example only |
| 1503-60 | Funnel - 60° approx - long stem - 60 mm diameter |
| 1503-75 | Funnel - 60° approx - long stem - 75 mm diameter |
| 1503-90 | Funnel - 60° approx - long stem - 90 mm diameter |
| 1504-40 | Funnel - 60° approx - short stem - 40 mm diameter |
| 1504-50 | Funnel - 60° approx - short stem - 50 mm diameter |
| 1504-60 | Funnel - 60° approx - short stem - 60 mm diameter |
| 1504-90 | Funnel - 60° approx - short stem - 90 mm diameter |
| 1511-32 | Funnel - filter - 32 ml |
| 5102-60 | Funnel - 60 degrees approx - long stem - 60 mm diameter - ground 19/26 |

Hydrometers

| Code | Description |
|---------------|---|
| LA.HY.BR5+5 | Stevenson Reeves Hydrometer5 to 5 |
| | Specification: Reeves Brix 20°C Basis of Scale: °Brix For use at 20°C and at a surface tension of 45mN/m Lower Limit of Scale: -5 °Brix Upper Limit of Scale: +5°Brix Division Interval: 0.1 °Brix Maximum Permitted Error: ±0.2 °Brix Comes with a Works Certificate of Conformance The hydrometers have been manufactured and tested to the above specification and calibrated with reference to UKAS Traceable Instruments |
| LA.HY.BR.0-10 | Stevenson Reeves Hydrometer - 0 to 10 |
| | Specification: Reeves Brix 20°C Basis of Scale: °Brix For use at 20°C and at a surface tension of 45mN/m Lower Limit of Scale: 0 °Brix Upper Limit of Scale: 10°Brix Division Interval: 0.1 °Brix Maximum Permitted Error: ±0.2 °Brix Comes with a Works Certificate of Conformance The hydrometers have been manufactured and tested to the above specification and calibrated with reference to UKAS Traceable Instruments |
| LA.HY.BR.10-2 | Stevenson Reeves Hydrometer5 to +5 |
| | Specification: Reeves Brix 20°C Basis of Scale: °Brix For use at 20°C and at a surface tension of 45mN/m Lower Limit of Scale: 10 °Brix Upper Limit of Scale: 20°Brix Division Interval: 0.1 °Brix Maximum Permitted Error: ±0.2 °Brix Comes with a Works Certificate of Conformance The hydrometers have been manufactured and tested to the above specification and calibrated with reference to UKAS Traceable Instruments |

Jacket Tubes

| Code | Description |
|---------|--|
| 5082-03 | Jacket Tube - 19/26 - 40mm Jacket Tube - 19/26 - 40mm (Length of lower tube) Used on Thermometer Standard ground mouth |
| 5082-04 | Jacket Tube - 24/29 - 40mm Jacket Tube - 24/29 - 40mm (Length of lower tube) Used on Thermometer Standard ground mouth |

Magnetic Stir Bars

| Code | Description |
|------|---|
| B150 | Magnetic Stir Bar - 15mm (length) X 7mm (diameter) |
| B180 | Magnetic Stir Bar - 18mm (length) X 7mm (diameter) |
| B220 | Magnetic Stir Bar - 22mm (length) X 7mm (diameter) |
| B263 | Magnetic Stir Bar - 26.3 mm (length) X 7mm (diameter) |
| B275 | Magnetic Stir Bar - 27.5 mm (length) X 9 mm (width) |
| B300 | Magnetic Stir Bar - 30 mm (length) X 7mm (diameter) |
| B330 | Magnetic Stir Bar - 33 mm (length) X 7mm (diameter) |
| B360 | Magnetic Stir Bar - 36mm (length) X 9mm (diameter) |
| B485 | Magnetic Stir Bar - 48.5mm (length) X 9mm (diameter) |
| B565 | Magnetic Stir Bar - 56.5mm (length) X 9mm (diameter) |
| B660 | Magnetic Stir Bar - 66mm (length) X 9mm (diameter) |
| B988 | Magnetic Stir Bar - 98.8mm (length) X 10mm (diameter) |

Measuring Cylinders

| Code | Description |
|-----------|-------------------------------|
| 1601-0010 | Measuring cylinder - 0010 ml |
| | Graduated interval: 0.5ml |
| ĮĮ. | Capacity tolerance: ±0.5 ml |
| 50.77 | Width of graduation: ≤ 0.4 mm |
| | Image is example only |
| 1601-0025 | Measuring cylinder - 0025 ml |
| | Graduated interval: 0.5ml |
| | Capacity tolerance: ±0.5 ml |
| | Width of graduation: ≤ 0.4 mm |
| 1601-0050 | Measuring cylinder - 0050 ml |
| | Graduated interval: 1 ml |
| | Capacity tolerance: ±0.5 ml |
| | Width of graduation: ≤ 0.4 mm |
| 1601-0100 | Measuring cylinder - 0100 ml |
| | Graduated interval: 1ml |
| | Capacity tolerance: ±1 ml |
| | Width of graduation: ≤ 0.4 mm |
| 1601-0500 | Measuring cylinder - 0500 ml |
| 11 | Graduated interval: 5 ml |
| 122 | Capacity tolerance: ±5 ml |
| | Width of graduation: ≤ 0.5 mm |
| | Image is example only |

| Code | Description |
|------------|---|
| 1611-0100 | Measuring cylinder - graduate - 0100 ml |
| | Graduated interval: 10 ml |
| | Capacity tolerance: ±1.5 ml |
| | Width of graduation: ≤ 0.4 mm |
| 1611-0250 | Measuring cylinder - graduate - 0250 ml |
| | Graduated interval: 25 ml |
| | Capacity tolerance: ±3 ml |
| | Width of graduation: ≤ 0.5 mm |
| 1601H-0025 | Measuring cylinder - Hexagonal base - 0025 ml |
| | Graduated interval: 5 ml |
| | Capacity tolerance: ±0.5 ml |
| | Width of graduation: ≤ 0.4 mm |
| | Image is example only |
| 1601H-0050 | Measuring cylinder - Hexagonal base - 0050 ml |
| | Graduated interval: 1 ml |
| | Capacity tolerance: ±0.5 ml |
| | Width of graduation: ≤ 0.4 mm |
| 1601H-0100 | Measuring cylinder - Hexagonal base - 0100 ml |
| | Graduated interval: 1 ml |
| | Capacity tolerance: ±1 ml |
| | Width of graduation: ≤ 0.4 mm |
| 1601H-0250 | Measuring cylinder - Hexagonal base - 0250 ml |
| | Graduated interval: 2 ml |
| | Capacity tolerance: ±2 ml |
| | Width of graduation: ≤ 0.4 mm |
| 1601H-0500 | Measuring cylinder - Hexagonal base - 0500 ml |
| | Graduated interval: 5 ml |
| | Capacity tolerance: ±2.5 ml |
| | Width of graduation: ≤ 0.4 mm |

| Code | Description |
|-----------|---|
| 1603-0100 | Measuring cylinder - with stopper - 0100 ml |
| <u>@</u> | Graduated interval: 1 ml |
| | Capacity tolerance: ±0.5 ml |
| | Width of graduation: ≤ 0.4 mm |
| 1603-0250 | Measuring cylinder - with stopper - 0250 ml |
| | Graduated interval: 2 ml |
| | Capacity tolerance: ±1 ml |
| | Width of graduation: ≤ 0.4 mm |

Miscellaneous

| Code | Description |
|-----------|--|
| 1788-1-5 | Oil determining tube - 5 ml |
| 5036-1 | Splash proof bulb - 19/26, 19/26 |
| 1325-0300 | U Tube - Drying Tube - 13mm OD - 300 x 60mm U Tube 13mm outside diameter - 300mm long by 60mm wide with 5mm OD side tubes and ground glass stoppers. Used as a drying tube or suitable as a manometer. |
| 1326-0300 | U Tube - Drying Tube 13mm OD - 300 x 75mm U tube 13mm outside diameter - 300mm long, 75mm wide with 7mm side tubes and ground glass stoppers. This tube is manufactured for us for use as a manometer, but is also used as a drying tube. |

Mortar

| Code | Description |
|------------|-------------------------------------|
| 1383-12060 | Mortar - glass pestle - 120 X 60 mm |
| | |
| 1383-18096 | Mortar - glass pestle - 180 X 96 mm |

Panel Testing

| Code | Description |
|-------------|---|
| SYA-SS-DK25 | Surface Soundness Disks *25 |
| | 25 * Disks for surface soundness testing of MDF and Particleboard |

Petri Dish



Pipettes

| Code | Description |
|-----------|---|
| 1456 | Pipette - dropping - straight tip |
| 1630A-001 | Pipette - measuring - 001 ml |
| 1630A-002 | Pipette - measuring - 002 ml |
| 1630A-010 | Pipette - measuring - 010 ml |
| 1630A-025 | Pipette - measuring - 025 ml |
| 1630A-050 | Pipette - measuring - 050 ml |
| 1633A-001 | Pipette - volumetric - 001 ml Capacity tolerance: ±0.007 ml Flow rate: 7-12 seconds Width of graduation: ≤ 0.4 mm |
| 1633A-002 | Pipette - volumetric - 002 ml Capacity tolerance: ±0.01 ml Flow rate: 7-12 seconds Width of graduation: ≤ 0.4 mm |
| 1633A-003 | Pipette - volumetric - 003 ml Capacity tolerance: ±0.015 ml Flow rate: 15-25 seconds Width of graduation: ≤ 0.4 mm |

| Code | Description |
|------------|--|
| 1633A-005 | Pipette - volumetric - 005 ml |
| 1000,1 000 | Capacity tolerance: ±0.015 ml |
| | Flow rate: 15-25 seconds |
| | Width of graduation: $\leq 0.4 \text{ mm}$ |
| 1633A-010 | Pipette - volumetric - 010 ml |
| 1000/1 010 | Capacity tolerance: ±0.02 ml |
| | Flow rate: 20-30 seconds |
| | Width of graduation: $\leq 0.4 \text{ mm}$ |
| 1633A-015 | Pipette - volumetric - 015 ml |
| | Capacity tolerance: ±0.025 ml |
| | Flow rate: 20-30 seconds |
| | Width of graduation: $\leq 0.4 \text{ mm}$ |
| 1633A-020 | Pipette - volumetric - 020 ml |
| 1000/1 010 | Capacity tolerance: ±0.03 ml |
| | Flow rate: 25-35 seconds |
| | Width of graduation: ≤ 0.4 mm |
| 1633A-025 | Pipette - volumetric - 025 ml |
| | Capacity tolerance: ±0.03 ml |
| | Flow rate: 25-35 seconds |
| | Width of graduation: ≤ 0.4 mm |
| 1633A-050 | Pipette - volumetric - 050 ml |
| | Capacity tolerance: ±0.05 ml |
| | Flow rate: 30-40 seconds |
| | Width of graduation: $\leq 0.4 \text{ mm}$ |
| 1633A-100 | Pipette - volumetric - 100 ml |
| | Capacity tolerance: ±0.08 ml |
| | Flow rate: 35-45 seconds |
| | Width of graduation: ≤ 0.4 mm |

Separating Funnel

| Code | Description |
|----------|---|
| 5103-100 | Funnel - seperatory - constant pressure - cylindrical -100ml- ground glass joints top and bottom 19/26 |
| | Note: This is a restricted item. To ensure that purchases are for legal uses only, we ask that you contact us first for clearance. |
| 1546-250 | Funnel - seperatory - cylindrical - graduated - ground in glass stopper and stopcock - 250 ml |
| | Image is example only |
| | Note: This is a restricted item. To ensure that purchases are for legal uses only, we ask that you contact us first for clearance. |
| 1546-500 | Funnel - seperatory - cylindrical - graduated - ground in glass stopper and stopcock - 500 ml |
| | Note: This is a restricted item. To ensure that purchases are for legal uses only, we ask that you contact us first for clearance. |
| 1546-125 | Funnel - seperatory - cylindrical - graduated - ground in glass stopper and stopcock - 125 ml |
| | Note: This is a restricted item. To ensure that purchases are for legal uses only, we ask that you contact us first for clearance. |
| 1544-125 | Funnel - seperatory - pear shape - graduated - ground in glass stopper and stopcock - 125 ml |
| | Note: This is a restricted item. To ensure that purchases are for legal uses only, we ask that you contact us first for clearance. |
| 1544-250 | Funnel - seperatory - pear shape - graduated - ground in glass stopper and stopcock - 250 ml |
| 1544-500 | Funnel - seperatory - pear shape - graduated - ground in glass stopper and stopcock - 500 ml |

Slides

| Code | Description |
|------|--|
| 7201 | Cover slip - 18x18 mm Microscope slide cover slips 500 per box |
| 7104 | Microscope slides - double concave - ground edges Microscope slides - double concave - ground edges - Box of 50 |
| 7105 | Microscope slides - frosted Microscope slides - frosted - box of 50 |
| 7107 | Microscope slides - frosted one end both sides Microscope slides - frosted one end both sides - box of 50 |
| 7101 | Microscope slides - ground edges Microscope slides - ground edges - Box of 50 pc |
| 7103 | Microscope slides - single concave - ground edges Microscope slides - single concave - ground edges - Box of 50 |
| 7102 | Microscope slides - ungrounded edges Microscope slides - ungrounded edges - box of 50 |

Stands and Accessories

| Code | Description |
|---------|--|
| 4682-3A | Retort Ring - Plain stem - 050mm Retort rings, Rings, with plain stem 8mm dia. with welded joints for greater strength. Diameter 50mm |
| 4682-3B | Retort Ring - Plain stem - 075mm |
| 4682-3C | Retort Ring - Plain stem - 100mm |
| 4682-3D | Retort Ring - Plain stem - 125mm |
| 4682-3E | Retort Ring - Plain stem - 150mm Retort rings, Rings, with plain stem 8mm dia. with welded joints for greater strength. Diameter 150mm |
| 4670-01 | Retort Stand - Adjustable Base Retort Stand, Rectangular, complete with rod, base made of mild steel plate with hammer finish and hole. Iron rod 12.5 mm dia. and nickel-plated provided with locked pin for extra tightening of rod. Base fitted with levelling screw and feet. Base size 200 x 125mm, Rod Length 600mm |
| 4673-02 | Retort Stand - Pressed Steel Retort Stand, Rectangular pressed steel with mat blue finish, hole is located centrally on the length. Base size 200 x 125mm, Rod Length 600mm |
| 4694 | Universal Clamp Universal clamp Made of sheet metal and chrome plated, spring controlled jaws cork lined which can accept 12 to 50mm dia. articles, with brass wing nut, fitted with 150mm long mild steel rod. |

Stands and Accessories

| Code | Description |
|---------|---|
| 4697 | Retort Clamp - Die-cast |
| | Retort clamp, Die-cast in alloy, with other parts plated, clamp accepts articles from 2-90mm dia., actuated by nickel plated pummels and twin screw. The design of the jaw ensures a firm grip at all angles of opening. The cork liners for the jaws are well secured. Fitted with 150mm long rod. |
| 4701 | Retort Clamp - Three Prong |
| | Retort clamp, Three Prong, die-cast in alloy, with other parts plated brass, clamp accepts articles up to 75mm dia., actuated by nickel plated pummels and twin screw. Jaws are covered in rubber. Fitted with 150mm long rod. |
| 4685-4A | Retort ring with boss head on stem - 50mm Diameter |
| | |
| 4685-4B | Retort ring with boss head on stem - 75mm Diameter |
| 4685-4C | Retort ring with boss head on stem - 100mm Diameter |
| 4685-4D | Retort ring with boss head on stem - 125mm Diameter |
| 4685-4E | Retort ring with boss head on stem - 150mm Diameter |

Stirrers

| Code | Description |
|-----------|--|
| 1294-0007 | Stirrer rod - 7-8 X 330 mm Stirrer rod - 7-8 X 330 mm |

Stoppers

| Code | Description |
|---------|--------------------------------|
| 5065-01 | Stopper Glass - 10/19 - ground |
| 5065-02 | Glass stopper 14/23, Ground |
| 5065-03 | Glass stopper 19/26, Ground |
| 5065-05 | Glass stopper 29/32, Ground |
| 5065-06 | Stopper Glass - 34/35 - ground |
| 5065-07 | Stopper Glass - 40/38 - ground |
| 5065-08 | Stopper Glass - 50/42 - ground |

Test tubes

| Code | Description |
|--------------|---|
| 1232-12100 | Test tube - with rim - 12 X 100 mm |
| 1232-13100 | Test tube - with rim - 13 X 100 mm |
| 1232-15150 | Test tube - with rim - 15 X 150 mm |
| 1232-16125 | Test tube - with rim - 16 X 125 mm |
| 1232-16125-1 | Test tube - with rim - 16 X 125 mm 100x pack of 100 units |
| 1232-16150 | Test tube - with rim - 16 X 150 mm |
| 1232-16155 | Test tube - with rim - 16 X 155 mm |
| 1232-18150 | Test tube - with rim - 18 X 150 mm |
| 1232-25150 | Test tube - with rim - 25 X 150 mm |
| 1232-25150 | Test tube - with rim - 25 X 150 mm x 100 |
| 1231-10100 | Test tube - without rim - 10 X 110 mm |
| 1231-11110 | Test tube - without rim - 11 X 110 mm |
| 1231-1275 | Test tube - without rim - 12 X 075mm |
| 1231-12100 | Test tube - without rim - 12 X 100 mm |
| 1231-13130 | Test tube - without rim - 13 X 150 mm |
| 1231-15100 | Test tube - without rim - 15 X 100 mm |
| 1231-25150 | Test tube - without rim - 25 X 150 mm |
| 1231-25150 | Test tube - without rim - 25 X 150 mm x 100 |

Thermometers

| Code | Description |
|---------|--|
| TM-900 | TM-900 Handset Thermometer |
| 111 300 | Handset thermometer with an LCD display and an external temperature probe. |
| | Temperature range: -50 to 150 degrees. |
| | |

Watchglasses

| Code | Description |
|----------|----------------------|
| 1175-080 | Watch glass - 080 mm |
| 1175-090 | Watch glass - 090 mm |
| 1175-100 | Watch glass - 100 mm |
| 1175-120 | Watch glass - 120 mm |



VITIS & WINEMAKERS NZ Office & Shop:

73 Grove Road, Mayfield, Blenheim. New Zealand **Phone:** +64 3 577-8778

Head Office:

96 Chifley Drive, Preston. VIC. Australia

Phone: +61 (03) 9487-1160

info@vitiswinemakers.com www.vitiswinemakers.com